Industrial Tablet PC for true mobility



TraffiCom[™]

THE WIRELESS CLIENT FOR EXTREME ENVIRONMENTS





Shark. The Ultraslim Tablet PC for demanding environments.

Shark is a rugged light weight industrial Tablet PC that brings added mobility and ease of use to all types of industrial and commercial applications. Shark's big advantage is that it can be used in so many ways. It is easy to carry and use by hand and it can be attached to a computer hook that lightens the load and lets operators work comfortably with their hands free for as long as they need to. It can easily be connected to vehicles with via a docking station.

Flexible and portable. Shark is available with a wide range of accessories for true flexibility. Shark's accessories include vehicle docking station, table stand, port replicator, wearable solutions, WLAN, WAN and Bluetooth. With Shark you can collect and receive data wherever it is required. A bright, high contrast touch screen makes viewing data easy from any angle or light condition.

Continuos. Shark has a "hot-swap" function which enables you to switch batteries without rebooting. The Lithium Ion battery guarantees many hours of operation.

Extreme. The rugged design including IP65 protection enables you to use TraffiCom Shark exactly where you need it without worrying about limitations due to dust, rain, cold or heat. TraffiCom Shark has been tested for shock and vibration according to military standards and withstands multiple drops on concrete.

Easy. Data can be inputted via a touch screen, 10 hotkeys or an external keyboard. Data can also be captured by connecting barcode or RFID readers.

Specifications	
Operating System	Windows XP Embedded Windows XP Pro
Display	8.4" colour TFT SVGA 800x600, 220 NIT
Processor	800 MHz Transmeta Crusoe TM5800, 512 KB cache
Chipset	VIA VT82686B
RAM	Standard 256 MB (Optional 512 MB)
Graphics	Silicon Motion SMI 722 Lynx3DM+, 8MB
Touch screen	Resistive 8-wire Touch Screen
Sound	Soundblaster Pro & AC97 compatible
Storage	One Compact flash type II, One Compact flash type I Optional: 20 GB rotating hard disk
PC-Card slot	One type II 32-bit Cardbus or 16-bit PCMCIA
Ports	1 USB Type 1.1A, 1 FireWire Type iLink, 1 Docking Connector, Type 26 pin MDR (Available through the port replicator*: Power Input, CRT Output, PS/2 Mouse, PS/2 Keyboard, USB 1.1, Stereo line out, Stereo line in and Mic in)
Power Supply	Internal Battery 3700 mAh, 11.1V, Hot swappable 50W External Power 18.5V±10% Vehicle Dock 9-36V 65W (isolated)* AC/DC power adaptor 100-240V 50-60 Hz*
Temperature	Non operating -30°C to 60°C, Operating 5°C to 50°C, Operating with less battery performance -20°C to 50°C, Operating and charging -10°C to 35°C, Non-operating and charging 5°C to 45°C
Sealing Level	IP65 (with lids closed), Water and Dust Protected
Drop test	3 feet on concrete (26 directions/drops)
Dimensions & Weight	Metal housing with shock absorbing handles 1.6 kg, 250 \times 180 \times 39 mm

^{*}optional accessories

CONSAFE LOGISTICS AB DEPT. LOGISTIC EQUIPMENT ADDRESS Porfyrvägen 14, SE-224 78 Lund, Sweden PHONE +46-(0)46-280 04 00 FACSIMILE +46-(0)46-32 52 18 E-MAIL info@trafficom.com www.trafficom.com www.consafelogistics.com

