

## Imaje Nova Series

*Combining high-performance capabilities in a compact, robust, modern design*



The Imaje Nova printer family is for customers who need high speed, large label rolls, reliability, and great ease of use. The printers in the Nova series are the most compact printers in their class. Featuring all-metal casing, they are tough enough for harsh industrial environments, yet quiet enough for office use.

### Imaje Nova Series

- Robust, high-performance range of thermal transfer and direct thermal printers
- 3 different print widths: 104 mm (4.1") - 168 mm (6.6") - 216 mm (8.5")
- Print resolution: 200 dpi or 300 dpi
- Print speed: up to 250 mm/sec
- Prints texts, logos, barcodes and graphics
- 10 scalable fonts as standard
- Most barcodes, including several 2-dimensional and stacked codes (QR code, PDF 417, Datamatrix, Maxicode, etc.)
- 2 high speed serial interfaces, USB and Ethernet ports

For printing labels  
tickets and tags



Thermal Printer Range

# Imaje Nova Series

*Combining high-performance capabilities in a compact, robust and modern design*

## Imaje Nova Series

*High performance and user friendly*



Imaje Nova Series printers are **easy to operate**, even for non-technical people. For high-performance printing, they are **exceptionally versatile**, meeting the requirements of most user applications

- Big power supply enables printing at high speed (up to 250 mm/sec, 10 ips) on the entire surface of labels
- Optimized print cycle: enhanced print speed
- Big roll (150 mm is standard; 215 mm optional): very little down-time for reloading
- Open paper path for fast reloading
- Open media roll for fast reloading
- 3 different media positioning sensors are standard (short, long and black-mark); changing media type is faster as it does not require changing the sensor
- Print roll can be removed without special tools: speeds up maintenance
- Special non-stick surface coating from Imaje simplifies cleaning
- Webservice and built-in set-up program requires little software education for operators

## Imaje Nova Series

*Robust and easy to integrate*

Imaje Nova Series printers are **designed to fit into many different systems** at varying levels of integration and meet a range of connectivity requirements

- All-metal construction
- Suitable for desktop or built-in applications, thus always enabling the best installation possible (particularly interesting for integrators)
- Wid-range of interfaces (two high-speed serial ports, USB-port, Ethernet-port): connects to all systems
- Automatic 110-240 VAC regulator adapts to different voltages; the same printer works all over the world without cumbersome external boxes



## Technical specifications

### Imaje Nova4 DT



<b>Technology</b> DIRECT THERMAL	<b>Height</b> 150 MM (5.9")	<b>Width</b> 232 MM (9.1")	<b>Depth</b> 360 MM (14.2")
<b>Weight</b> 5.8 KG (12.8 LBS)	<b>Print resolution</b> 200 DPI OR 300 DPI	<b>Maximum print width</b> 104 MM (4.1")	<b>Print speed</b> UP TO 250 MM/S (10 IPS)

### Imaje Nova4 TT



<b>Technology</b> THERMAL TRANSFER	<b>Height</b> 210 MM (8.3")	<b>Width</b> 240 MM (9.4")	<b>Depth</b> 360 MM (14.2")
<b>Weight</b> 7.2 KG (15.9 LBS)	<b>Print resolution</b> 200 DPI OR 300 DPI	<b>Maximum print width</b> 104 MM (4.1")	<b>Print speed</b> UP TO 200 MM/S (8 IPS)

### Imaje Nova6 DT



<b>Technology</b> DIRECT THERMAL	<b>Height</b> 150 MM (5.9")	<b>Width</b> 292 MM (11.5")	<b>Depth</b> 360 MM (14.2")
<b>Weight</b> 6.8 KG (15 LBS)	<b>Print resolution</b> 200 DPI	<b>Maximum print width</b> 168 MM (6.6")	<b>Print speed</b> UP TO 200 MM/S (8 IPS)

### Imaje Nova6 TT



<b>Technology</b> THERMAL TRANSFER	<b>Height</b> 210 MM (8.3")	<b>Width</b> 315 MM (12.4")	<b>Depth</b> 360 MM (14.2")
<b>Weight</b> 8.2 KG (18.1 LBS)	<b>Print resolution</b> 200 DPI	<b>Maximum print width</b> 168 MM (6.6")	<b>Print speed</b> UP TO 200 MM/S (8 IPS)

### Imaje Nova8 DT



<b>Technology</b> DIRECT THERMAL	<b>Height</b> 150 MM (5.9")	<b>Width</b> 345 MM (13.5")	<b>Depth</b> 360 MM (14.2")
<b>Weight</b> 7 KG (15.5 LBS)	<b>Print resolution</b> 200 DPI	<b>Maximum print width</b> 216 MM (8.5")	<b>Print speed</b> UP TO 150 MM/S (6 IPS)

## Printing

- 10 scalable fonts as standard: Univers Medium - Univers Bold - Univers Condensed - Univers Condensed Bold - CG Times - CG Times Italic - CG Times Bold - CG Times Bold Italic - Letter Gothic Bold - Coronet
- Supports English and all European languages including Greek and Cyrillic characters
- Most current barcodes are available including several two-dimensional and stacked codes: QR code, PDF 417, Datamatrix, Maxicode, etc.
- Prints lines, boxes and frames - Graphics in all four directions
- Can receive compressed graphics for fast Windows printouts

## Media

- Die cut labels, continuous roll, fanfold tickets and tags
- Minimum length: 10 mm (0.39") - Maximum length: unlimited

	Imaje Nova4 DT	Imaje Nova4 TT	Imaje Nova6 DT	Imaje Nova6 TT	Imaje Nova8 DT
Minimum width	40 mm (1.5")	40 mm (1.5")	40 mm (1.5")	40 mm (1.5")	150 mm (5.9")
Maximum width	115 mm (4.5")	115 mm (4.5")	180 mm (7.1")	180 mm (7.1")	230 mm (9.1")

- Thickness: 58  $\mu\text{m}$  (0.0023") to 180  $\mu\text{m}$  (0.0071")
- Core diameter: minimum 40 mm (1.5") - Not for Nova8 DT
- Maximum label roll diameter: up to 215 mm (8.5") - Not for Nova8 DT
- Fanfold media (Nova8 DT)

## Programming language

- Communication in printable ASCII characters
- File management for macros and graphics
- Field rotation 0°, 90°, 180°, 270°
- Status request
- Built in real time clock
- 10 individual, programmable counters

## Communication interface

- Two serial interfaces, 300-115 200 bps
- USB interface
- Bi-directional Centronics (option)
- Ethernet: TCP/IP (LPD, R Telnet, FTP, Webserver)

## Other characteristics

- Options: 215 mm paper roll kit (not for Nova8 DT) - Peel-off kit (Not for Nova8 DT) - LTS - Bi directional Centronix interface - Daisy chain cable.
- 32-bit RISC Processor - 2 MB flash memory - 512 KB SRAM - 2 MB DRAM
- Unique Printing method reduces memory need and increases print cycle speed
- Built in configuration program
- Operating system stored in flash PROM, for easy software upgrades
- Works internally with Unicode character set
- Time and date symbols
- Backwards compatible with the Markpoint MkII series
- Power requirements: 110/240 VAC  $\pm$  15%, 50-60 Hz
- Operating temperature range: +5°C to +40°C
- Operating humidity: 20% to 85% non-condensing relative humidity

## Label design software

- MP Design, Codesoft, Label Matrix, Nice Label
- Most label design software using graphics mode

Imaje reserves the right to modify product design and/or characteristics at any time without notice.



A DOVER COMPANY

### Imaje Nordic AB

Thermal printer group  
Säterigatan 20  
417 64 Göteborg  
Sweden

Tel.: +46 31 656900

Fax: +46 31 656983

E-mail: [sales@nordic.imaje.com](mailto:sales@nordic.imaje.com)

<http://www.imaje.se>

You make it, we mark it.



Optimize printer availability, plus save on repair and replacement costs - that is the CareAdvantage you get when you extend your already unrivalled printer warranty from **Imaje Worldwide Service.**