


4 LOAD CELL LOW PROFILE SCALES



Measurement with application of 4 load cells is a guarantee of precise readout, no matter of place of loading the mass on the weighing pan. Low profiled scales can be used in fairly dry conditions (low humidity of environment). Construction of scale is made of mild steel. Height of weighing platform is 50 mm. Aluminum pan is made in anti slippery version (with max capacity of 300 kg) or steel with anti slippery layer (for scales with higher capacities). The LCD indicator is installed on a three meter long cable with possibility of hanging it on the wall.

Scale equipped with drive through is a very useful weighing device, which can be installed in technological line (no need to order pit version). Scale is powered from mains, RS 232 as standard equipment.



Counting pieces



Checkweighing



Summing function



2 years warranty period

Technical data:

	WPT/4F 60 C5	WPT/4F 150 C5	WPT/4F 60 C6	WPT/4F 150 C6	WPT/4F 300 C6	WPT/4F 600 C6
Max capacity	60 kg	150 kg	60 kg	150 kg	300 kg	600 kg
Readability	20 g	50 g	20 g	50 g	100 g	200 g
Tare range	-60 kg	-150 kg	-60 kg	-150 kg	-300 kg	-600 kg
Platform size	600×600 mm	600×600 mm	800×800 mm	800×800 mm	800×800 mm	800×800 mm
Working temperature	-10° - +40 °C					
Output signal	RS 232					
IP rating	IP 65 construction, IP 54 indicator					
Power supply	230V AC/11V AC 50Hz and 6×AA					
Display	LCD (backlit)					

Technical data:

	WPT/4F 60 C7	WPT/4F 150 C7	WPT/4F 300 C7	WPT/4F 600 C7	WPT/4F 300 C8	WPT/4F 600 C8	WPT/4F 600 C9
Max capacity	60 kg	150 kg	300 kg	600 kg	300 kg	600 kg	600 kg
Readability	20 g	50 g	100 g	200 g	100 g	200 g	200 g
Tare range	-60 kg	-150 kg	-300 kg	-600 kg	-300 kg	-600 kg	-600 kg
Platform size	1000×1000 mm	1000×1000 mm	1000×1000 mm	1000×1000 mm	1200×1200 mm	1200×1200 mm	1500×1500 mm
Working temperature	-10° - +40 °C						
Output signal	RS 232						
IP rating	IP 65 construction, IP 54 indicator						
Power supply	230V AC/11V AC 50Hz and 6×AA						
Display	LCD (backlit)						

Additional equipment:

RACK FOR HEAD

LCD ADDITIONAL DISPLAY

LARGE SIZE ADDITIONAL DISPLAY

"KAFKA" THERMAL PRINTER

NEEDLE PRINTER "EPSON"

RAMPS FOR LOW PROFILED SCALE

COMPUTER SOFTWARE: PW-WIN 2005

COMPUTER SOFTWARE: RAD-KEY 2000

COMPUTER SOFTWARE: REC-FS 2000

COMPUTER SOFTWARE: LS-FS 2000

RS 232/RS 485 CONVERTER

DISTRIBUTOR: